

DEQ AIR QUALITY PROGRAM
1410 N. Hilton, Boise, ID 83706
For assistance, call the 373 449
Air Permit Hotline–1-877-5PERMIT

# **PERMIT TO CONSTRUCT APPLICATION**

Revision 4

Please see instructions on page 4 before filling out the form.

MAY - 7 2007

SENERAL INFORMA	IION	DEPARTMENT OF ENVIRONMENTAL QUALITY STATE A Q PROGRAM
Company Name:	Doloughan Const LCC DBA L	ost River Ready Mix
Facility Name:	Mackay Plant	Facility ID No: # 130
Brief Project Description:	Consteuct operate a Portuble Co	nchate Batch Pikint Facility leady Mix Conclute & Precast on Site Mater
Mailing Address:	898 Lembi Dil	Eme. 12 R. Deberghan & Yahro. Com
Alty:	Salmon FD	State: Idaho
Zip Code:	83467.	County: USA.
General Nature of Business & Products:	Ready Mix Concrete and Procost	Products.
	194/5//	
Contact Name, Title:	Roll Dolonghan Presiden	
Phone:		delt:08/940-0650
Email:	R. Doloughan & Yakoo Com	
Owner or Responsible Official Name, Title:	Bory Deloughan - President Cassic Soloughan Frons uper	2 .
hone:	(208) 940-0650	
Email:	R. Doloughan & Yahoo Com.	
Proposed Initial Plant .ocation:	7 mi South Mackay " See	10911 TON 25E
Vearest City:	Mackay	- [4] 하는 사이 [1] 1 전 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -
County:	Custer.	Startup Date: ASAP. 18 - June - July 07
Reason for Application:	Permit to construct a new source  Permit to operate an existing unpermitted so	
	Permit to modify/revise an existing permitte  Permit No.:	d source (identify the permit below)
	Issue Date: Facility ID:	
Check here to indica	te you would like to review a draft permit prior to	final issuance.
Comments: 15 day Applica	2 4 16 2-7	

## **CONCRETE BATCH PLANT INFORMATION**

~	and the second	and the second	3 1 1 Lat 1 1 Aug.	200
4%	8 " M. W. W. C. W.	men D.	advisor to the	Bear in 16
1	Concr	ELECTION	CELL IN C.	242611

Manufacturer:	England Wal	ding & Octors	han lons	Model: N/A	
Manufacture Date:	Copportly	rder Consti	entror		
Maximum Hourly Thro		75 (cy/hou	with the second		
Maximum Daily Throu	ighput:	<i>9.00</i> (cy/day	)		
Maximum Annual Thro	oughput: 65	1000(cy/yea	r)		
Requested Annual Th	roughput: $I\mathcal{O}$	COO (cy/yea	r)		
2a. Cement Storag	je Silo Bagho	ouse No.			
Manufacturer:	Fastway	and the same of th		Model: Silo # 4	
Stack Height from Gro	ound: 3 <i>[* 8]</i>	(ft)	TO ONCE COMPANY OF STREET WAS AND AND A STREET OF STREET, AND A STREET,	Exit Air Flow Rate:	(acfm) 2450 CFM Me
Stack Inside Diameter	: 85"	(ft)		* PM <sub>10</sub> Control Efficiency:	(%) 99.8
* Manufacturer Grain I	Loading Guara	ntee:			antonno mana 12 metro de mande de mante de mande
* Attach manufacturer's	PM <sub>10</sub> control ef	ficiency if avai	lable.		
2b. Cement Storag	je Silo Bagho	ouse No.			
Manufacturer:			1	Model:	
Stack Height from Gro	ound:	(ft)	İΛ	Exit Air Flow Rate:	(acfm)
Stack Inside Diameter	**	(ft)		* PM <sub>10</sub> Control Efficiency:	(%)
* Manufacturer Grain I	Loading Guara	ntee:			
* Attach manufacturer's	Pivi <sub>10</sub> control et	ficiency if avail	lable.		
				illo Baghouse No.	
Attach manufacturer's  2c. Cement Supple  Manufacturer:					
2c. Cement Supple	ement (such			illo Baghouse No.  Model: Exit Air Flow Rate:	(acfm)
2c. Cement Supple	ement (such :	as flyash) S		Model: Exit Air Flow Rate;	(acfm)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter:	ement (such i	as flyash) S		Model:	(acfm) (%)
2c. Cement Supple Manufacturer: Stack Height from Gro	ement (such i	(ft) (ft) ntee:	torage S	Model: Exit Air Flow Rate;	
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's	ement (such a bund: : : Loading Guara PM <sub>10</sub> control eff	(ft) (ft) ntee:	torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:	
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I	ement (such a bund: : : Loading Guara PM <sub>10</sub> control eff	(ft) (ft) ntee:	torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:	***************************************
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's 2d. Cement Supple	ement (such a bund: : : Loading Guara PM <sub>10</sub> control eff ement (such a	(ft) (ft) ntee:	torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:	(%)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I * Attach manufacturer's 2d. Cement Supple Manufacturer:	ement (such and a such	as flyash) S  (ft) (ft) ntee: ficiency if avail	torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  iilo Baghouse No. Model: Exit Air Flow Rate:	(%) (acfm)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I. * Attach manufacturer's  2d. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter:	ement (such a bund: : : Loading Guara : :PM <sub>10</sub> control eff : : : : :	as flyash) S  (ft) (ft) (ntee: ficiency if avail as flyash) S  (ft) (ft)	torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  iilo Baghouse No. Model:	(%)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's 2d. Cement Supple Manufacturer: Stack Height from Gro	ement (such a bund: : Loading Guaran PM <sub>10</sub> control eff ement (such a bund: : Loading Guaran	(ft) (ft) (ntee:   ficiency if avail as flyash) S (ft) (ft) (ft) (ft)	torage S lable. torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  iilo Baghouse No. Model: Exit Air Flow Rate:	(%) (acfm)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I * Attach manufacturer's  2d. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I	ement (such a bund:	(ft) (ft) (ntee:   ficiency if avail as flyash) S (ft) (ft) (ft) (ft)	torage S lable. torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  iilo Baghouse No. Model: Exit Air Flow Rate:	(%) (acfm)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I. * Attach manufacturer's  2d. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I. * Attach manufacturer's	ement (such a bund:	(ft) (ft) (ntee:   ficiency if avail as flyash) S (ft) (ft) (ft) (ft)	torage S lable. torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  iilo Baghouse No. Model: Exit Air Flow Rate:	(%) (acfm)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's  2d. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's  3. Weigh Batcher E	ement (such and such	(ft) (ft) (ntee:   ficiency if avail as flyash) S (ft) (ft) (ft) (ft)	torage S lable. torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  iilo Baghouse No. Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:	(%) (acfm) (%)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I. * Attach manufacturer's  2d. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain I. * Attach manufacturer's  3. Weigh Batcher E Manufacturer:	ement (such a such a su	as flyash) S  (ff) (ff) ntee: ficiency if avail as flyash) S  (ff) (ff) (ft) ficiency if avail	torage S lable. torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  illo Baghouse No. Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  Model: Exit Air Flow Rate:	(%) (acfm) (%)
2c. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's  2d. Cement Supple Manufacturer: Stack Height from Gro Stack Inside Diameter: * Manufacturer Grain L * Attach manufacturer's  3. Weigh Batcher E Manufacturer: Stack Height from Gro	ement (such a bund:	as flyash) S  (ft) (ft) (ft) (ft) (ft) (ft) (ft) (ft	torage S lable. torage S	Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:  illo Baghouse No. Model: Exit Air Flow Rate: * PM <sub>10</sub> Control Efficiency:	(%) (acfm) (%)

## **ELECTRICAL GENERATOR SET INFORMATION (if applicable)**

Manufacturer:			N	fodel:	(CERTACOLORS)	
Maximum Rated Capa	city:	1	□нр	□kW	ng manjanjanjanjanjanjanjanjanjanjanjanjanja	
Fuel Type:		☐ Gasoline/\	☐ Diesel	☐ Natural Gas ☐ Propane	<b>KONTINUMANINANI</b>	
Maximum Fuel Usage	Rate:		☐ gal./hr.	☐ cfh	annintengantarakanan	
Maximum Daily Hrs. of	f Operations:	/// /(hours/c	(yet			
Maximum Annual Hrs.	of Operations:	UV (hours/y	/ear)		***************************************	
Stack Parameters:	C Parameters: Stack Height from Ground (find Stack Inside Diameter (find Stack Inside			Stack Exhaust Flow Rate (acfm): Stack Exhaust Gas Temperature (°F):		
ADDITIONAL GENER	ATOR (if app	licable)			990000000000000000000000000000000000000	
Manufacturer:				Model:	***********	
Maximum Rated Capac	city:		□Нр	☐ kW		
Fuel Type:		☐ Gasoline	☐ Diesel	☐ Natural Gas ☐ Propane		
Maximum Fuel Usage	Rate:		│ gal./hr.	☐ cfh		
Maximum Daily Hrs. of	f Operations:	\ (hours/	\ (hours/day)			
Maximum Annual Hrs.	of Operations:	/(hours/	(høurs/year)			
Stack Parameters:		from Ground (ft): ide Diameter (ft):		Stack Exhaust Flow Rate (acfm): Stack Exhaust Gas Temperature (°F):	***************************************	
\$1,000 PTC applic	ation fee enclo	sed				
Certification of Truth, I hereby certify that bas contained in this and ar IDAPA 58.01.01,123-12 Responsible Official Signatur Roll 1 Dolons Print or Type Responsible Of	sed on information and attached and attached and attached and attached and attached	on and belief forr	med after resocument(s) a	nsible Official) easonable inquiry, the statements and information are true, accurate, and complete in accordance with	h	



**Department of Environmental Quality** 1410 N. Hilton Boise, ID 83706

For assistance, call the Air Permit Hotline: 1-877-5PERMIT

#### DEO - AIR QUALITY PROGRAM PORTARIE FOUIPMENT RELOCATION FORM

Company Name: Defoughan Ronst LLC DBA Lost Rues Ready Mr.							
Phone Number: (208) 940 - 0650							
Mailing Address: 898 fem hi Rd Salmon Id 83467							
Contact: Roly Dolonghan							
Signature: Date: 5/07/07							
Plant Type Conclute Batch Plants							
(HMA, Rock Crusher, Mfr., Model No.)							
Type of Permit Dermit to Construct or Yes No If Yes, Facility ID: TBD							
Permit by Rule Yes No If Yes, Facility ID:							
Fuel Type for Generator:							
Have any major components of the plant or its air pollution equipment been replaced or modified since the plant last operated? Yes No If Yes, attach explanation on additional paper.							
Current Location, include county and nearest city: Sec 104/1 The 25E 7m. South Hay 93							
New Location, include county and nearest city: Same as above.							
Estimated Startup Date: Estimated End Date:							
(month/day/year) Jone 07 (month/day/year) of							
Will Plant be co-located with another rock crusher, concrete batch, or hot-mix asphalt plant at new Yes location?							
Name of Other Company:							
Type of Plant: □ Rock Crusher □ Concrete Batch □ Hot-Mix Asphalt Yes							
Type of Operating Permit To Construct Yes No 11 Yes, Facility 1D.							
Permit by Rule Yes No If Yes, Facility ID:							
Will plant be operated in conjunction with a state of Idaho contract?  No							
If Contract No.:							
Yes State of Idaho Contact Person: Phone Number:							
Priorie Number.							

#### THIS FORM MUST BE SUBMITTED TEN (10) DAYS BEFORE PLANT IS RELOCATED.

A scaled plot plan identifying the property boundary of the new site must be included with this form (see Permit Application Form PP-Plot Plan for guidance).

Mail to:

**Air Quality Program Office - Application Processing** 


**Department of Environmental Quality** 

1410 North Hilton Boise, ID 83706-1255

Or, Fax to:

208-373-0340

Attn: Air Quality Program Office - Application Processing



# AIR DISPERSION MODELING PROTOCOL: REQUEST TO USE DEQ GENERIC MODELING RESULTS TO DEMONSTRATE PRECONSTRUCTION COMPLIANCE WITH IDAHO AIR QUALITY RULES.

Proposed Project: Portable Concrete Batch Pla		cy/HR <u>~ /</u>		_cy/YR	
Location: (if portable, identify initial location)	7mi South Howy	93 From Mack	cy Idaho S	ec 10911 60	U 250

- 1) An emissions inventory (EI) developed by DEQ based on the plant's capacity and proposed maximum daily and annual operations will be included with the application, and will comply with the following:
  - a. Emissions will be calculated using AP-42 emission factors and good engineering judgement.
  - b. Fugitive emissions sources will be included in the EI, except for emissions resulting from vehicle traffic and wind erosion from storage piles.
  - c. The level of emissions control assumed for each source will be clearly specified.
  - d. Cr+6 will be presumed to comprise 20% of the total chromium emissions from cement silo filling, and 30% of the total chromium emissions from cement supplement (flyash) silo filling.
- 2) The proposed project will meet all of the criteria specified below, and (Applicant name) agrees to accept permit conditions requiring continuing compliance with the physical parameters and setback distance(s) described in Table 1. (Applicant name) is requesting that the DEQ generic model results be used to demonstrate preconstruction compliance with NAAQS and TAPs for this project. No additional modeling analysis will be submitted for this project.

Table 1. CRITERIA FOR USING DEQ'S CONCRETE BATCH PLANT GENERIC MODELING RESULTS FOR AIR IMPACT ANALYSES

		IMPACT A	NALYSES		
Parameter		Generic Mod		Proposed Project	
Concrete batch plant type and capacity	Truck mix (redi-mix or dry mix) or Central mix				TRUCK MIX
Operation in any PM <sub>10</sub> nonattainment area	Not proposed.			NOT PROPOSED	
Presence of an electric generator.	No generator. Line power is available.			LINE POWE	
No Collocation.  Minimum distance from nearest edge of any emissions source to any other source of emissions, including another concrete batch plant, hot mix asphalt plant, or rock crushing plant.	200 meters (656 feet)			> 656	
Number of cement and/or cement supplement storage silos	Not limited. The model layout assumes all silo en that cement/supplement is not transferred between				
Maximum daily concrete production (cy/day)	1,500 2,400 3,600 4,800				75 cy/hr X 24
Minimum Setback Distance.  Minimum distance from nearest edge of any emissions source to a receptor. <sup>a</sup>	40 m 60 m 100 m 150 m (131 ft) (197 ft) (328 ft) (492 ft)		>40m		
Maximum annual concrete production (cy/year)	300,000	400,000	500,000	500,000	~ 10,000
Cement and supplement storage silo baghouse(s) Minimum stack height (height above ground) Minimum PM/PM <sub>10</sub> control	10 meters (32.8 ft) 99%			~ 37A	
Weigh hopper loading baghouse, or equivalent Minimum stack height (height above ground) Minimum PM/PM <sub>10</sub> control	10 meters (32.8 ft) 99%			~12ft	
<u>Truck-mix loadout or Central Mix loading.</u> Minimum PM/PM <sub>10</sub> control.	95% Boot enclosure, shroud, water sprays, or baghouse/cartridge filter			500 t	
Transfer Point Fugitives. Minimum PM/PM <sub>10</sub> control.	75% Water sprays, enclosures, shrouds, or aggregate/sand is damp on an as-received basis and used before significantly drying out.			wet aggregate hand hoses	

minimi i ivi i irili vonuor	basis and used before significantly drying out.	Man de la
		RDoloughan@yahoo.com
Rory Doloughan	Dobu show Const UC DSH best Cover	Karel 208.940.0650
Print Name	Company	Telephone/E-mail
	President	5/7/27
Signature	Title/Position	/ / Date

FAY To: (208) 373-0340

ATTN: Cheryl Robinson

PAGE ? - THE CHALLIS MESSENGER - THURSDAY, MAY 10, 2007



LEGAL NOTICE

Lost River Ready Mix has applied for an air quality permit to construct and operate a portable concrete batch plant at the location of NW ½ SW ½ Section 11 Township 6 N 25 E. The meeting will be held at the Mackay Kids Park at 9 a.m., Monday, May 21st, 2007

Publish: May 10, 2007

Proof of legal to be published this Thursday. May 10, 2007

Please call with questions/changes

Thank you,

Sheri Kemmerer

(208) 879-4445



## **IDAHO DEPARTMENT OF ENVIRONMENTAL QUALITY**

1410 North Hilton Boise, Idaho 83706-1253

RECEIPT

		and desired to the second seco	EIPT		57/07 ATE
RECEIVED FROM	n Dolo	rugha	v Cons	truction	LC
SOURCE  Cash	Check [년	Money O	order □ No.	102	2
DESCRIPTION		7 .	enteres entre	AMOU	NT OF PAYMENT
PTC	Apple	cetton	)		0000 00
And the residence of the state	anne ann an Aireann ann an Aireann an Aireann ann an Aireann an Aireann an Aireann an Aireann an Aireann an Ai				
					····
					-
	ence equipment quantitative receives account or the distribution of an informative interest and effect by their	adamantahan dan kepinan madamban seminah adamban seminah adamban dapat ang upis adamban dapat dapat dapat dapa			
	-	estimation contraction commission contraction and and an analysis of the contraction and an artificial and artificial artificial and artificial and artificial and artificial and artificial and artificial artificial and artificial artificial artificial artificial and artificial artifi			
RECEIVED BY	ye	<b>\$</b>	TOTAL RECEIVED	> 10	500 0
PID	OBS	CA	SUB-OBJ	WP	BE